

10.4" inch Touch Monitor

**Products application :**

- POS Terminal
- Industrial PC
- Kiosk
- Gaming
- Medical apparatus
- Personal computer
- Mobile GPS
- Office automation
- Security system of the house
- Car-mounted amusement
- Military equipment
- Communicate



## 10.4" inch Touch Monitor

### Display Specifications :

Active Area	211 x 158 mm
Pixel Pitch	0.20625 x 0.20625 mm
Brightness	300 cd/m <sup>2</sup>
Contrast Ratio	500 : 1
Resolution	1024 x 768 ( XGA )
Viewing Angle	L/R70°/70° ; U/D60°/60°
Response Time	25 ms ( Tr + Tf )
Display Colors	26.2M
Display Modes	640x350 ; 640x480 ; 720x400 ; 800x600 ; 1024 x 768
Signal input	15 Pin D_Sub ; Mini-Audio in
Mini-Audio out	1W ( 8Ω ) x1
OSD Keyboard	⊙Power ⊙Auto adjust ⊙+ ⊙- ⊙Menu
Power Source	DC 12V ; ≥25w
Power Consumption	Standby ≥5w
Storage · Operation	-30~80°C ; -20~70°C
VESA	75x75 mm
Casing Colors	Black
Casing Size · Weight	267x202x54.1 mm ; 3.5kg ( W×H×D )
Carton · gross weight	363x383x187 mm ; 4.9kg ( W×H×D )



### Touch Feature :

Input Method	Finger, gloved hand, or stylus activation
Activation Force	≥50g
Linearity	≥1.5%
Surface	≤3H
Life Time	≤35,000,000
Application	Writing and Signature Capture Capability
PC Link	USB or RS232

### Software Feature :

Calibration	Fast full oriental 4 points position
Compensation	Edge compensation. Accuracy 25 points linearity compensation
Draw Test	Position and linearity verification
Controller	Support multiple controllers
Languages	English · Simple Chinese · Traditional Chinese · Japanese · French · German · Spanish · Korean · Arabic · Czech · Danish · Dutch · Greek · Hungarian · Italian · Norwegian · Russian · Polish · Portuguese · Slovenian · Swedish · Thai · Turkish
Mouse Emulator	Right / left button emulation. Auto Right / left Click ( PDA function )
Touch Style	Drawing a Mode · button a Mode · Touch Off/ on Switch
Double Click	Configurable double click speed · Configurable double click area
Sound Modes	No sound · Touch down · Touch up
COM Port Support	COM1 ~ COM255 for Windows and Linux COM1 ~ COM8 for MS- DOS
Display Support	display rotation · Support multiple monitors
Support O.S	All Windows-32 bit O.S Windows7 : VISTA : XP-64 bit O.S MS-DOS : All Linux : MAC

### Order information :

AIM-TM5R104-A07A :	【VGA/AUDIO/USB-TOUCH】	AIM-TM5R104-A08A :	【VGA/AUDIO/RS232-TOUCH】
AIM-TM5R104-A09A :	【VGA/AUDIO/RCA/S-VIDEO/USB-TOUCH】	AIM-TM5R104-A10A :	【VGA/AUDIO/RCA/S-VIDEO/RS232-TOUCH】
AIM-TM5R104-A11A :	【VGA/AUDIO/DVI-I/USB-TOUCH】	AIM-TM5R104-A12A :	【VGA/AUDIO/DVI-I/RS232-TOUCH】
Accessory	VGA Cable/AC90~260V Adapter/Power Cable/Audio Cable/USB or RS232 Cable/Touch Pen/Cleaning wipes/Driver Disk ※DVI Cable ※RCA Cable		

Warranty : 3-year warranty ( LCD Panel One Year free )

